

**AKG**

HEADPHONES

MICROPHONES

WIRELESS

INTEGRATED SYSTEMS



# P420

## HIGH-PERFORMANCE MULTIPATTERN CONDENSER MICROPHONE

[Features](#) [Specs](#) [Downloads](#)

<b>GENERAL</b>	Audio Frequency bandwidth	20 to 20000 Hz
	Sensitivity	28 mV/Pa
	Equivalent Noise Level	16 dB-A
	Signal to Noise	78 dB-A
	Preattenuation Pad	-20 dB
	Bass Cut Filter	300 Hz
	Electrical Impedance	200 Ohms
	Recommended Load Impedance	1000 Ohms
<b>POLAR PATTERNS</b>	Polar Pattern	omnidirectional; cardioid; figure eight
	Number	3
<b>POWERING INTERFACE</b>	Voltage	44 to 52 V
	Current	2 mA
<b>AUDIO OUTPUT</b>	Type	Balanced XLR
	Gender	Male
	Contacts	3-pin
<b>DESIGN</b>	Finish	metallic blue/nickel grille
<b>DIMENSIONS / WEIGHT</b>	Height	165 mm
	Diameter	53 mm
	Net Weight	525 g



### INCLUDED ACCESSORIES

**SH300**  
SPIDER SUSPENSION**Metal carrying case**  
CARRYING CASE

### OPTIONAL ACCESSORIES

**W4000**  
WINDSCREEN**ST305**  
TABLE STAND