



# Q-12S / Q-28S

Two passive Subs are available for the Q-3 system including Q-12S and Q-28S. Those woofers respectively features 12" and 2 x 8" transducers for a rated power of 300 W each. A pole mount system is available on both boxes for portable compact systems with four satellites.

	Q-12S	Q-28S
<b>System Type</b>	12" Passive Vented Subwoofer	2x8 " Passive Bandpass Subwoofer
<b>Rated Power</b>	300W Continuous; 600W program	300W Continuous; 600W program
<b>Sensitivity</b>	122dB continuous; 125dB peak	121dB continuous; 124dB peak
<b>Frequency Response</b>	45Hz - 2.8kHz (+/-10dB)	52Hz - 800Hz (+/-10dB)
<b>Impedance</b>	4 $\Omega$	8 $\Omega$
<b>Transducer</b>	12" Ferrite Woofer , 2.55" voice coil	2x8" Ferrite Woofer , 2" voice coil
<b>Input Connector</b>	4 PIN Terminal Block and 2 x NL-4 Speakon	4 PIN Terminal Block and 2 x NL-4 Speakon
<b>Enclosure</b>	Plywood Cabinet, Resistant Black Paint, Metal Grille	Plywood Cabinet, Resistant Black Paint, Metal Grille
<b>Mounting</b>	One metal Standard Pole-mount	One metal Standard Pole-mount
<b>Dimensions</b>	500 x 350 x 542 mm (19.69" x 13.78" x 21.33")	510 x 250 x 540 mm (20.08" x 9.84" x 21.26")
<b>Net Weight</b>	20.1 kg (44.1 lbs)	18.5 kg (40.78 lbs)

*Specifications subject to modification without notice*

Q-12S



Q-28S

